



Rear Discharge Manure Spreader

With years of experience and a reputation for quality, NC have produced an extensive range of manure spreaders to include five models: 7m³, 9m³, 11m³, 13m³ and 15m³ - suitable for small farmers to large contractors.



Build quality ensures low running costs, a consistent and even discharge, with the ability to handle virtually all types of waste, ie semi-solid, poultry litter, industrial sludges, waste products etc. The unique rotor design and blade pattern allows you to spread all types of manures without the trouble and fuss of changing spreader decks and the large 'cubic capacities' available are particularly suited to low density manures.

NC's reputation for quality has stood the test of time with 30 year old machines still working today!



WHERE QUALITY COMES FIRST



Rear Discharge Manure Spreader

Standard Features

- Heavy duty monocoque body construction
- Variable speed floor chains with reverse option functions
- 4 Heavy duty stress relieved 14x50 chains (24.5 tonne breaking strain each) on 9m³, 11m³, 13m³, and 15m³.
- 2 Heavy duty stress relieved 14x50 chains (24.5 tonne breaking strain each) on 7m³.
- Floor chains protected by a cross-line relief valve
- Galvanised quick attach floor slots (no welding to the chain)
- Galvanised rear vertical auger frame
- Balanced twin vertical augers with reversible hardox blades
- 10mm thick auger flights
- Heavy duty 150mm square 10 stud axle with hydraulically operated brakes on 9m³, 11m³, 13m³, and 15m³.
- Heavy duty 120mm square 8 stud axle with hydraulically operated brakes on 7m³.
- Full road lighting (with automatic covers to lights when spreading with slurry door fitted)
- Remote greasing for drive shaft and auger bearings
- Wide angle PTO with shear bolt
- 1000rpm
- Removable Drawbar stand

Optional Equipment

- Hydraulically operated slurry door
- Canopy only
- Rear Drawbar with hydraulic brake connection and 7 pin socket
- 8" extension sides
- Electric remote control (in cab) for variable floor speed
- Toolbox
- Swivel Drawbar eye attachment
- Sprung Drawbar
- Steel guard for PTO shaft
- Non standard finish colours
- Wheel options
- Spares pack
- Drive shaft slip clutch



4 floor chains for strength and durability

MODEL	7m ³	9m ³	11m ³	13m ³	15m ³
Rated load carrying capacity	6000 kg	8000 kg	10000 kg	12000 kg	14000 kg
Capacity (heaped)	7m ³	9m ³	11m ³	13m ³	15m ³
Spread width	Up to 16m	Up to 16m	Up to 16m	Up to 16m	Up to 16m
Axle Beam Size	90mm	150mm	150mm	150mm	150mm
Brake Size	400 x 80	420 x 180	420 x 180	420 x 180	520x180
A (Width)	2550mm (8' 4")	2687mm (8' 10") 2877mm (9' 5 1/4")	2877mm (9' 5 1/4") 2990mm (9' 9 3/4") TBC	299mm (9' 9 3/4") TBC TBC	TBC TBC TBC
Tyre Size	420/85/R34 (Std)	18.4/34 14Ply (Std) 580/70 R38(option)	580/70 R38 (Std) 650/75 R32 (option) 750/60 R30.5 (option)	650/75 R32 (Std) 750/60 R30.5 (option) 850/50 R30.5 (option)	560/60 R22.5 (Std) 600/55 R26.5 cross Ply(option) 600/55 R26.5 Radial(option)
Body Size L x W x H (internal)	3490 x 1500 x 755mm	4400 x 1500 x 910mm	4750 x 1500 x 1110mm	5350 x 1500 x 1110mm	5730 x 1500 x 1140mm
B (Side Loading Height)	1785	1960	2200	2200	TBC
Floor Drive	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Floor Drive control	Hydraulic Variable c/w reverse Electric Option	Hydraulic Variable c/w reverse Electric Option	Hydraulic Variable c/w reverse Electric Option	Hydraulic Variable c/w reverse Electric Option	Hydraulic Variable c/w reverse Electric Option
Floor Chain Size	14 x 50mm	14 x 50mm	14 x 50mm	14 x 50mm	14 x 50mm
No of Floor Chains	2	4	4	4	4
PTO input speed	1000rpm	1000rpm	1000rpm	1000rpm	1000rpm
Un-laden Weight	Approx. 4500kg	Approx. 5000kg	Approx. 5500kg	Approx. 5800kg	Approx. 6200kg



NC ENGINEERING (HAMILTONSBAWN) LTD

2 Killyrudden Road, Hamiltonsbawn, Richhill, Co. Armagh, N. Ireland BT61 9SF
 Tel: 028 3887 1970 Fax: 028 3887 0362
 E.mail:info@nc-engineering.com website: www.nc-engineering.com

In accordance with our policy of continued development we reserve the right to alter specifications and designs without notice